


Code: LPXUS2PB-PBB

Linea-Perlina CFX | LINEA-PERLINA CFX RANGE | Power Sockets

Product Image



Wiring



Dimensions

Insert Type	1 gang 2A Unswitched Socket
Insert Colour	Black
EAN13 Barcode	5017504871048
Commodity Code	85363010
Luckins TSI	391658080
ETIM Class	EC000125
Dimensions(Nominal)	Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips
Minimum Wall Box Depth	35mm
Switched Poles	None
Current Rating	2 Amp
Voltage	220/250V AC
Maximum Load	2 Amp
Mains Frequency	50Hz
IP Rating	IP2XD
Contact Gap Minimum	None
Terminal Capacity 1	5 x1mm ²
Terminal Capacity 2	4x1.5mm ²
Terminal Capacity 3	2x2.5mm ²
Terminal Capacity 4	1x4mm ²
Earth Terminal Capacity 1	5x1mm ²
Earth Terminal Capacity 2	4 x 1.5mm2
Earth Terminal Capacity 3	2 x 2.5mm2
Earth Terminal Capacity 4	1 x 4mm2
Product Class 1	Must be earthed
Ambient Operating Temperature	-5° to +40°C
Recommended Location	Internal Use Only
Maximum Installation Altitude	2000m
Standard/Approval	BS 546
Additional Notes	Shuttered: Yes

DATASHEET


Code: LPXUS2PB-PBB

Linea-Perlina CFX | LINEA-PERLINA CFX RANGE | Power Sockets

Hamilton[®]
LINEA PERLINA CFX
US2
Unswitched Socket

Patents And Trade Marks

Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588



R Hamilton & Co Ltd, Unit 10 Carrick Business Centre,
4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

E: info@hamilton-litestat.com | **W:** www.hamilton-litestat.com

(WEB)

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 29/04/2024 E&OE