# **DATASHEET**




Code: LPXUS5PB-ABW

## Linea-Perlina CFX | LINEA-PERLINA CFX RANGE | Power Sockets

### **Product Image**



#### Wiring



#### Dimensions

Insert Type	1 gang 5A Unswitched Socket
Insert Colour	White
EAN13 Barcode	5017504890056
Commodity Code	85363010
Luckins TSI	391658161
ETIM Class	EC000125
Dimensions(Nominal)	Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips
Minimum Wall Box Depth	35mm
Switched Poles	None
Current Rating	5 Amp
Voltage	220/250V AC
Maximum Load	5 Amp
Mains Frequency	50Hz
IP Rating	IP2XD
Contact Gap Minimum	None
Terminal Capacity 1	5 x1mm²
	5 x1mm <sup>2</sup> 4x1.5mm <sup>2</sup>
Terminal Capacity 1	
Terminal Capacity 1 Terminal Capacity 2	4x1.5mm²
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3	4x1.5mm <sup>2</sup> 2x2.5mm <sup>2</sup>
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4	4x1.5mm <sup>2</sup> 2x2.5mm <sup>2</sup> 1x4mm <sup>2</sup>
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Earth Terminal Capacity 1	4x1.5mm <sup>2</sup> 2x2.5mm <sup>2</sup> 1x4mm <sup>2</sup> 5x1mm <sup>2</sup>
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Earth Terminal Capacity 1 Earth Terminal Capacity 2	4x1.5mm <sup>2</sup> 2x2.5mm <sup>2</sup> 1x4mm <sup>2</sup> 5x1mm <sup>2</sup> 4 x 1.5mm2
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3	4x1.5mm <sup>2</sup> 2x2.5mm <sup>2</sup> 1x4mm <sup>2</sup> 5x1mm <sup>2</sup> 4 x 1.5mm2 2 x 2.5mm2
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4	4x1.5mm <sup>2</sup> 2x2.5mm <sup>2</sup> 1x4mm <sup>2</sup> 5x1mm <sup>2</sup> 4 x 1.5mm2 2 x 2.5mm2 1 x 4mm2
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Product Class 1 Ambient Operating	4x1.5mm² 2x2.5mm² 1x4mm² 5x1mm² 4 x 1.5mm2 2 x 2.5mm2 1 x 4mm2 Must be earthed
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Product Class 1 Ambient Operating Temperature	4x1.5mm²  2x2.5mm²  1x4mm²  5x1mm²  4 x 1.5mm2  2 x 2.5mm2  1 x 4mm2  Must be earthed  -5° to +40°C
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Product Class 1 Ambient Operating Temperature Recommended Location Maximum Installation	4x1.5mm²  2x2.5mm²  1x4mm²  5x1mm²  4x1.5mm2  2x2.5mm2  1x4mm2  Must be earthed  -5° to +40°C  Internal Use Only

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road Brislington Bristol BS4 5N7

T: +44 (0)1747 860088

: info@hamilton-litestat.com | W: www.hamilton-litestat.con

(WFR)


All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 05/05/2024 F&OF

# **DATASHEET**



Code: LPXUS5PB-ABW

## Linea-Perlina CFX | LINEA-PERLINA CFX RANGE | Power Sockets



#### **Patents And Trade Marks**

Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588

T: +44 (0)1747 860088

: info@hamilton-litestat.com | W: www.hamilton-litestat.cor