DATASHEET




Code: LRXC11BC-BSB

Linea-Rondo CFX | LINEA-RONDO CFX RANGE | Hotel Card Switch with LED

Product Image



Wiring



Dimensions

Insert Type	1 gang 10A (6AX) Card Switch On/Off with Blue LED Locator
Insert Colour	Bright Chrome/Black
EAN13 Barcode	5017504501914
Commodity Code	85363010
Luckins TSI	391677854
ETIM Class	EC000029
Dimensions(Nominal)	Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips
Minimum Wall Box Depth	35mm
Switched Poles	Single
Current Rating	10A (6AX)
Voltage	220/250V AC
Maximum Load	10 Amp (6 Amp inductive)
Mains Frequency	50Hz
IP Rating	IP2XD
IP Rating Contact Gap Minimum	IP2XD 3mm
-	
Contact Gap Minimum	3mm
Contact Gap Minimum Terminal Capacity 1	3mm 3x1mm²
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2	3mm 3x1mm² 2x1.5mm²
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3	3mm 3x1mm² 2x1.5mm² 1x2.5mm²
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1	3mm 3x1mm² 2x1.5mm² 1x2.5mm² 5x1mm²
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2	3mm 3x1mm² 2x1.5mm² 1x2.5mm² 5x1mm² 4 x 1.5mm2
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3	3mm 3x1mm² 2x1.5mm² 1x2.5mm² 5x1mm² 4 x 1.5mm2 3 x 2.5mm2
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4	3mm 3x1mm² 2x1.5mm² 1x2.5mm² 5x1mm² 4 x 1.5mm2 3 x 2.5mm2 1 x 4mm2 Multi-strand
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5	3mm 3x1mm² 2x1.5mm² 1x2.5mm² 5x1mm² 4 x 1.5mm2 3 x 2.5mm2 1 x 4mm2 Multi-strand 1 x 6mm2
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating	3mm 3x1mm² 2x1.5mm² 1x2.5mm² 5x1mm² 4 x 1.5mm2 3 x 2.5mm2 1 x 4mm2 Multi-strand 1 x 6mm2 Must be earthed
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature	3mm 3x1mm² 2x1.5mm² 1x2.5mm² 5x1mm² 4 x 1.5mm2 3 x 2.5mm2 1 x 4mm2 Multi-strand 1 x 6mm2 Must be earthed -5° to +40°C


R Hamilton & Co Ltd, Unit 10 Carrick Business Centre,

DATASHEET



Code: LRXC11BC-BSB

Linea-Rondo CFX | LINEA-RONDO CFX RANGE | Hotel Card Switch with LED



Additional Notes

Adjustable Time Delay 10 seconds - 5 minutes. Suitable for 44mm and 54mm width Hotel Key Cards

Patents And Trade Marks

Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350

T: +44 (0)1747 860088

: info@hamilton-litestat.com | W: www.hamilton-litestat.con

(WFR

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.