DATASHEET




Code: LRXC11BK-PBB

Linea-Rondo CFX | LINEA-RONDO CFX RANGE | Hotel Card Switch with LED

Product Image



Wiring



Dimensions

| Insert Type | 1 gang 10A (6AX) Card Switch On/Off with Blue LED Locator |
|---|--|
| Insert Colour | Black Nickel/Black |
| EAN13 Barcode | 5017504381912 |
| Commodity Code | 85363010 |
| Luckins TSI | 391677935 |
| ETIM Class | EC000029 |
| Dimensions(Nominal) | Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm |
| Fixing Hole Centres | Box Fixing = 60.3mm Grid Fixing = CFX Clips |
| Minimum Wall Box Depth | 35mm |
| Switched Poles | Single |
| Current Rating | 10A (6AX) |
| Voltage | 220/250V AC |
| Maximum Load | 10 Amp (6 Amp inductive) |
| Mains Frequency | 50Hz |
| IP Rating | IP2XD |
| | |
| Contact Gap Minimum | 3mm |
| Contact Gap Minimum Terminal Capacity 1 | 3mm 3x1mm² |
| • | |
| Terminal Capacity 1 | 3x1mm² |
| Terminal Capacity 1 Terminal Capacity 2 | 3x1mm ² 2x1.5mm ² |
| Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 | 3x1mm ² 2x1.5mm ² 1x2.5mm ² |
| Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 | 3x1mm ² 2x1.5mm ² 1x2.5mm ² 5x1mm ² |
| Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 | 3x1mm ² 2x1.5mm ² 1x2.5mm ² 5x1mm ² 4 x 1.5mm2 |
| Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 | 3x1mm ² 2x1.5mm ² 1x2.5mm ² 5x1mm ² 4 x 1.5mm2 3 x 2.5mm2 |
| Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 | 3x1mm² 2x1.5mm² 1x2.5mm² 5x1mm² 4 x 1.5mm2 3 x 2.5mm2 1 x 4mm2 Multi-strand |
| Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 | 3x1mm² 2x1.5mm² 1x2.5mm² 5x1mm² 4 x 1.5mm2 3 x 2.5mm2 1 x 4mm2 Multi-strand 1 x 6mm2 |
| Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating | 3x1mm² 2x1.5mm² 1x2.5mm² 5x1mm² 4 x 1.5mm2 3 x 2.5mm2 1 x 4mm2 Multi-strand 1 x 6mm2 Must be earthed |
| Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature | 3x1mm² 2x1.5mm² 1x2.5mm² 5x1mm² 4 x 1.5mm2 3 x 2.5mm2 1 x 4mm2 Multi-strand 1 x 6mm2 Must be earthed -5° to +40°C |


R Hamilton & Co Ltd, Unit 10 Carrick Business Centre,

DATASHEET



Code: LRXC11BK-PBB

Linea-Rondo CFX | LINEA-RONDO CFX RANGE | Hotel Card Switch with LED



Additional Notes

Adjustable Time Delay 10 seconds - 5 minutes. Suitable for 44mm and 54mm width Hotel Key Cards

Patents And Trade Marks

Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350

T: +44 (0)1747 860088

: info@hamilton-litestat.com | W: www.hamilton-litestat.cor