DATASHEET




Code: LRXDPNBC-BSB

Linea-Rondo CFX | LINEA-RONDO CFX RANGE | Double Pole Switches

Product Image



Wiring



Dimensions

Incort Type	1 gang 20AY Double Pole Pocker + Noon
Insert Type	1 gang 20AX Double Pole Rocker + Neon
Insert Colour	Bright Chrome/Black
EAN13 Barcode	5017504506940
Commodity Code	85363030
Luckins TSI	391679661
ETIM Class	EC001590
Dimensions (Nominal)	Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips
Minimum Wall Box Depth	35mm
Switched Poles	Double
Current Rating	20AX
Voltage	220/250V AC
Maximum Load	20 Amp inductive
Mains Frequency	50Hz
IP Rating	IP2XD
Contact Gap Minimum	3mm
Terminal Capacity 1	3x2.5mm²
Terminal Capacity 2	2x4mm² Multi-strand
Terminal Capacity 3	1x6mm²
Earth Terminal Capacity 1	6x1mm²
Earth Terminal Capacity 2	5x1.5mm²
Earth Terminal Capacity 3	3x2.5mm²
Earth Terminal Capacity 4	2x4mm² Multi-strand
Earth Terminal Capacity 5	1x6mm²
Product Class 1	Must be earthed
Ambient Operating Temperature	-5° to +40°C
Recommended Location	Internal Use Only
Maximum Installation Altitude	2000m
Standard/Approval	BS EN 60669-1


R Hamilton & Co Ltd, Unit 10 Carrick Business Centre,

DATASHEET



Code: LRXDPNBC-BSB

Linea-Rondo CFX | LINEA-RONDO CFX RANGE | Double Pole Switches



Patents And Trade Marks

Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350

T: +44 (0)1747 860088

: info@hamilton-litestat.com | W: www.hamilton-litestat.cor