DATASHEET




Code: LRXSS1BC-BSB

Linea-Rondo CFX | LINEA-RONDO CFX RANGE | Power Sockets

Product Image



Wiring



Dimensions

Insert Type	1 gang 13A Double Pole Switched Socket
Insert Colour	Bright Chrome/Black
EAN13 Barcode	5017504506018
Commodity Code	85363010
Luckins TSI	391689091
ETIM Class	EC000125
Dimensions (Nominal)	Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips
Minimum Wall Box Depth	35mm
Switched Poles	Double
Current Rating	13 Amp
Voltage	220/250V AC
Maximum Load	13 Amp
Mains Frequency	50Hz
IP Rating	IP2XD
Contact Gap Minimum	3mm
Terminal Capacity 1	4x2.5mm²
Terminal Capacity 2	3x4mm²
Terminal Capacity 3	2x6mm² Multi-Strand
Terminal Capacity 4	1x10mm²
Earth Terminal Capacity 1	4x2.5mm²
Earth Terminal Capacity 2	3x4mm²
Earth Terminal Capacity 3	2x6mm² Multi-Strand
Earth Terminal Capacity 4	1x10mm²
Product Class 1	Must be earthed
Ambient Operating Temperature	-5° to +40°C
Recommended Location	Internal Use Only
Maximum Installation Altitude	2000m
Standard/Approval	BS 1363-2
Additional Notes	Dual Earth: Yes


R Hamilton & Co Ltd, Unit 10 Carrick Business Centre,

DATASHEET



Code: LRXSS1BC-BSB

Linea-Rondo CFX | LINEA-RONDO CFX RANGE | Power Sockets



Patents And Trade Marks

Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350

T: +44 (0)1747 860088

: info@hamilton-litestat.com | W: www.hamilton-litestat.cor