## **DATASHEET**




Code: LRXSS1BK-BKB

## Linea-Rondo CFX | LINEA-RONDO CFX RANGE | Power Sockets

#### **Product Image**



#### Wiring



### Dimensions

Insert Type	1 gang 13A Double Pole Switched Socket
Insert Colour	Black Nickel/Black
EAN13 Barcode	5017504532017
Commodity Code	85363010
Luckins TSI	391689169
ETIM Class	EC000125
Dimensions(Nominal)	Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips
Minimum Wall Box Depth	35mm
Switched Poles	Double
Current Rating	13 Amp
Voltage	220/250V AC
Maximum Load	13 Amp
Mains Frequency	50Hz
IP Rating	IP2XD
Contact Gap Minimum	3mm
Contact Gap Minimum  Terminal Capacity 1	3mm 4x2.5mm <sup>2</sup>
Terminal Capacity 1	4x2.5mm²
Terminal Capacity 1 Terminal Capacity 2	4x2.5mm² 3x4mm²
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3	4x2.5mm²  3x4mm²  2x6mm² Multi-Strand
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4	4x2.5mm²  3x4mm²  2x6mm² Multi-Strand  1x10mm²
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Earth Terminal Capacity 1	4x2.5mm²  3x4mm²  2x6mm² Multi-Strand  1x10mm²  4x2.5mm²
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Earth Terminal Capacity 1 Earth Terminal Capacity 2	4x2.5mm²  3x4mm²  2x6mm² Multi-Strand  1x10mm²  4x2.5mm²  3x4mm²
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3	4x2.5mm²  3x4mm²  2x6mm² Multi-Strand  1x10mm²  4x2.5mm²  3x4mm²  2x6mm² Multi-Strand
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4	4x2.5mm²  3x4mm²  2x6mm² Multi-Strand  1x10mm²  4x2.5mm²  3x4mm²  2x6mm² Multi-Strand  1x10mm²
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Product Class 1 Ambient Operating	4x2.5mm²  3x4mm²  2x6mm² Multi-Strand  1x10mm²  4x2.5mm²  3x4mm²  2x6mm² Multi-Strand  1x10mm²  Must be earthed
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Product Class 1 Ambient Operating Temperature	4x2.5mm²  3x4mm²  2x6mm² Multi-Strand  1x10mm²  4x2.5mm²  3x4mm²  2x6mm² Multi-Strand  1x10mm²  Must be earthed  -5° to +40°C
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Product Class 1 Ambient Operating Temperature Recommended Location Maximum Installation	4x2.5mm²  3x4mm²  2x6mm² Multi-Strand  1x10mm²  4x2.5mm²  3x4mm²  2x6mm² Multi-Strand  1x10mm²  Must be earthed  -5° to +40°C  Internal Use Only

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre,

**T:** +44(0)1747860088

: info@hamilton-litestat.com | W: www.hamilton-litestat.con

(1.450)


All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 27/04/2024/EACF.

# **DATASHEET**



Code: LRXSS1BK-BKB

## Linea-Rondo CFX | LINEA-RONDO CFX RANGE | Power Sockets



#### **Patents And Trade Marks**

Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350

**T:** +44 (0)1747 860088

: info@hamilton-litestat.com | W: www.hamilton-litestat.cor