# **DATASHEET**



Code: LRXTCMAB-SBB

# Linea-Rondo CFX | LINEA-RONDO CFX RANGE | Telephone and Data Outlets

### **Product Image**




#### Wiring

Pin No.	BT Wiring Schedule Colour Codes: Striped Wires	
$\Box$	GREEN / White	
2	BLUE / White	
3	ORANGE / White	
4	WHITE / Orange	
5	WHITE / Blue	
6	WHITE / Green	
Main Wire Colour shown in CAPITALS		

Incoming Telephone Cable On 4 wire systems, Pin 1 and 6 are not connected.

The maximum REN that can be connected to any one exchange line is 4. Any number of sockets may be connected. All sockets are connected in parallel. ie Pin 1 to Pin 1; Pin 2 to Pin 2; etc. as shown in the diagram above.

### **Dimensions**



Insert Type	1 gang Telephone Master
Insert Colour	Black
EAN13 Barcode	5017504471644
Commodity Code	85176990
Luckins TSI	391689680
ETIM Class	EC000018
Dimensions(Nominal)	Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips
Minimum Wall Box Depth	25mm
Switched Poles	N/A
Current Rating	n/a
IP Rating	IP2XD
Contact Gap Minimum	N/A
Earth Terminal Capacity 1	5x1mm²
Earth Terminal Capacity 2	4 x 1.5mm2
Earth Terminal Capacity 3	3 x 2.5mm2
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand
Earth Terminal Capacity 5	1 x 6mm2
Product Class 1	Must be earthed (ref BS7671 415.2.1)
Ambient Operating Temperature	-5° to +40°C
Recommended Location	Internal Use Only
Maximum Installation Altitude	2000m
Standard/Approval	BS 6312:2:2
Patents And Trade Marks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre,