# **DATASHEET**



Code: LRXTCMBK-BKB

# Linea-Rondo CFX | LINEA-RONDO CFX RANGE | Telephone and Data Outlets

### **Product Image**




#### Wiring

| Pin<br>No.                         | BT Wiring Schedule Colour Codes:<br>Striped Wires |  |
|------------------------------------|---|--|
| $\Box$                             | GREEN / White                                     |  |
| 2                                  | BLUE / White                                      |  |
| 3                                  | ORANGE / White                                    |  |
| 4                                  | WHITE / Orange                                    |  |
| 5                                  | WHITE / Blue                                      |  |
| 6                                  | WHITE / Green                                     |  |
| Main Wire Colour shown in CAPITALS |   |  |

Incoming Telephone Cable
On 4 wire systems, Pin 1 and 6
are not connected.

The maximum REN that can be connected to any one exchange line is 4. Any number of sockets may be connected. All sockets are connected in parallel. ie Pin 1 to Pin 1; Pin 2 to Pin 2; etc. as shown in the diagram above.

### Dimensions



| Insert Type                      | 1 gang Telephone Master   |
|----------------------------------|---|
| Insert Colour                    | Black   |
| EAN13 Barcode                    | 5017504531645   |
| Commodity Code                   | 85176990  |
| Luckins TSI                      | 391689761   |
| ETIM Class                       | EC000018  |
| Dimensions(Nominal)              | Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm  |
| Fixing Hole Centres              | Box Fixing = 60.3mm Grid Fixing = CFX Clips   |
| Minimum Wall Box Depth           | 25mm  |
| Switched Poles                   | N/A   |
| Current Rating                   | n/a   |
| IP Rating                        | IP2XD   |
| Contact Gap Minimum              | N/A   |
| Earth Terminal Capacity 1        | 5x1mm²  |
| Earth Terminal Capacity 2        | 4 x 1.5mm2  |
| Earth Terminal Capacity 3        | 3 x 2.5mm2  |
| Earth Terminal Capacity 4        | 1 x 4mm2 Multi-strand   |
| Earth Terminal Capacity 5        | 1 x 6mm2  |
| Product Class 1                  | Must be earthed (ref BS7671 415.2.1)  |
| Ambient Operating<br>Temperature | -5° to +40°C  |
| Recommended Location             | Internal Use Only   |
| Maximum Installation<br>Altitude | 2000m   |
| Standard/Approval                | BS 6312:2:2   |
| Patents And Trade Marks          | Linea is a Registered Trade Mark No 2398665 CFX is a<br>Registered Trade Mark No 2398667 Patent No. GB<br>2383375B Community Trd Mark No. 002906428<br>Linea-Rondo CFX is a UK Registered Design<br>Certificate No: R21=2106349 SS2=2106350 |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

E: info@hamilton-litestat.com | W: www.hamilton-litestat.cor

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 03/06/2024 ESOE