DATASHEET




Code: LSX1X2VAB-AB

Linea-Scala CFX | LINEA-SCALA CFX RANGE | Inductive Leading Edge Push On/Off Rotary 2 Way Switching Dimmers

Product Image



Wiring



Dimensions

| Insert Type | 1 gang 200VA Inductive Leading Edge Push On/Off Rotary 2 Way Switching Dimmer |
|----------------------------------|--|
| Insert Colour | Antique Brass |
| EAN13 Barcode | 5017504689117 |
| Commodity Code | 85365015 |
| Luckins TSI | 391701610 |
| ETIM Class | EC000025 |
| Dimensions(Nominal) | Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm |
| Fixing Hole Centres | Box Fixing = 60.3mm Grid Fixing = CFX Clips |
| Minimum Wall Box Depth | 35mm |
| Switched Poles | Single |
| Current Rating | 0.8 Amp |
| Voltage | 220/250V AC |
| Maximum Load | 200VA (low voltage) Min Load 25VA |
| Mains Frequency | 50Hz |
| IP Rating | IP2XD |
| Contact Gap Minimum | None |
| Terminal Capacity 1 | 2x1mm² |
| Terminal Capacity 2 | 2x1.5mm² |
| Earth Terminal Capacity 1 | 5x1mm² |
| Earth Terminal Capacity 2 | 4 x 1.5mm2 |
| Earth Terminal Capacity 3 | 3 x 2.5mm2 |
| Earth Terminal Capacity 4 | 1 x 4mm2 Multi-strand |
| Earth Terminal Capacity 5 | 1 x 6mm2 |
| Product Class 1 | Face plate must be earthed |
| Ambient Operating Temperature | -5° to +40°C |
| Recommended Location | Internal Use Only |
| Maximum Installation Altitude | 2000m |
| Standard/Approval | BS EN 60669-1 |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

E: info(a)hamilton-litestat.com | **W:** www.hamilton-litestat.coi

(WFR)

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 29/03/2024 EXOF.

DATASHEET



Code: LSX1X2VAB-AB

Linea-Scala CFX | LINEA-SCALA CFX RANGE | Inductive Leading Edge Push On/Off Rotary 2 Way Switching Dimmers



Additional Notes

LEADING EDGE TECHNOLOGY DIMMERS for use with low voltage toroidal transformers and some LED lamps. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. NOTE: It is recommended to contact the manufacturer of the transformer to confirm that it is dimmable and is considered to be an inductive load.

Patents And Trade Marks

Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588