DATASHEET



Code: LSXWR21BK-BSB

Linea-Scala CFX | LINEA-SCALA CFX RANGE | Wide Rocker Switches

Product Image



EAN13 Barcode 5051164014087 Commodity Code 85363010 Luckins TSI 408177700 ETIM Class EC001590 Dimensions(Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 4x1.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 6 1x6mm² Earth Terminal Capacity 7 1x4mm² Multi-strand Earth Terminal Capacity 8 1x6mm² Earth Terminal Capacity 9 1x6mm² Earth Terminal Capacity 1 1x6mm² Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating 1-5° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS EN 60669-1	_		
EAN13 Barcode 5051164014087 Commodity Code 85363010 Luckins TSI 408177700 ETIM Class EC001590 Dimensions(Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 4x1.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 6 1x6mm² Earth Terminal Capacity 7 1x4mm² Multi-strand Earth Terminal Capacity 8 1x6mm² Earth Terminal Capacity 9 1x6mm² Earth Terminal Capacity 1 1x6mm² Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating 1-5° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS EN 60669-1			
Commodity Code Luckins TSI 408177700 ETIM Class EC001590 Dimensions(Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 4x1.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 4 1x6mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 6 1x6mm² Earth Terminal Capacity 7 1x4mm² Multi-strand Earth Terminal Capacity 8 1x6mm² Earth Terminal Capacity 9 1x6mm² Earth Terminal Capacity 1 1x6mm² Earth Terminal Capacity 3 1x6mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 6 1x6mm² Earth Terminal Capacity 7 1x6mm² Earth Terminal Capacity 8 1x6mm² Earth Terminal Capacity 9 1x6mm² Earth Terminal Capacity 1 1x6mm² Earth Terminal Capacity 3 1x6mm² Earth Terminal Capacity 3 1x6mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 6 1x6mm² Earth Terminal Capacity 7 1x6mm² Earth Terminal Capacity 8 1x6mm² Earth Terminal Capacity 8 1x6mm² Earth Terminal Capacity 9 1x6mm²	Insert Colour	Black Nickel/Black	
Luckins TSI 408177700 ETIM Class EC001590 Dimensions(Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 4x1.5mm² Earth Terminal Capacity 4 4x1.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 6 1x6mm² Product Class 1 Must be earthed Ambient Operating 7emperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS EN 60669-1	EAN13 Barcode	5051164014087	
ETIM Class EC001590 Dimensions(Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 4x1.5mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 1x6mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating 1-5° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation Altitude SSEN 60669-1	Commodity Code	85363010	
Dimensions(Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth Switched Poles Single Current Rating 10AX Voltage Maximum Load 10 Amp inductive Mains Frequency 1P Rating IP 2XD Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 Earth Terminal Capacity 6x1mm² Earth Terminal Capacity 1 Earth Terminal Capacity 3 Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 Froduct Class 1 Must be earthed Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS EN 60669-1	Luckins TSI	408177700	
4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 1 Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 Earth Terminal Capacity 5 Foduct Class 1 Must be earthed Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS EN 60669-1	ETIM Class	EC001590	
Minimum Wall Box Depth Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 1x4mm² Multi-strand Earth Terminal Capacity 3 1x6mm² Earth Terminal Capacity 3 Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Forduct Class 1 Must be earthed Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS EN 60669-1	Dimensions(Nominal)		
Switched Poles Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal	Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 3 1x6mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS EN 60669-1	Minimum Wall Box Depth	25mm	
Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 3 1x6mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating -5° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS EN 60669-1	Switched Poles	Single	
Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 3 1x6mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating 7s° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS EN 60669-1	Current Rating	10AX	
Mains Frequency IP Rating IP Rating IP Rating IP Rating Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS EN 60669-1	Voltage	220/250V AC	
IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 3 1x4mm² Multi-strand Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating -5° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS EN 60669-1	Maximum Load	10 Amp inductive	
Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS EN 60669-1	Mains Frequency	50Hz	
Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating 75° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS EN 60669-1	IP Rating	IP2XD	
Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS EN 60669-1	Contact Gap Minimum	3mm	
Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating -5° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS EN 60669-1	Terminal Capacity 1	3x2.5mm²	
Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating -5° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS EN 60669-1	Terminal Capacity 2	1x4mm² Multi-strand	
Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating -5° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation 2000m Altitude Standard/Approval BS EN 60669-1	Terminal Capacity 3	1x6mm²	
Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating -5° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS EN 60669-1	Earth Terminal Capacity 1	6x1mm²	
Earth Terminal Capacity 4 Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval 1x4mm² Multi-strand 2v6mm² Internal Use Only 2000m BS EN 60669-1	Earth Terminal Capacity 2	4x1.5mm²	
Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating -5° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation 2000m Altitude Standard/Approval BS EN 60669-1	Earth Terminal Capacity 3	2x2.5mm²	
Product Class 1 Must be earthed Ambient Operating -5° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation 2000m Altitude Standard/Approval BS EN 60669-1	Earth Terminal Capacity 4	1x4mm² Multi-strand	
Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval Altitude Standard/Approval Standard/Approval -5° to +40°C 2000m Standard/Approval BS EN 60669-1	Earth Terminal Capacity 5	1x6mm²	
Temperature Recommended Location Internal Use Only Maximum Installation 2000m Altitude Standard/Approval BS EN 60669-1	Product Class 1	Must be earthed	
Maximum Installation 2000m Altitude Standard/Approval BS EN 60669-1	Ambient Operating Temperature	-5° to +40°C	
Altitude Standard/Approval BS EN 60669-1	Recommended Location	Internal Use Only	
	Maximum Installation Altitude	2000m	
Additional Notes CE Marked	Standard/Approval	BS EN 60669-1	
	Additional Notes	CE Marked	

Wiring

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre,

DATASHEET



Code: LSXWR21BK-BSB

Linea-Scala CFX | LINEA-SCALA CFX RANGE | Wide Rocker Switches

Dimensions	Patents And Trade Marks	Linea is a Registered Trade Mark No 2398665 CFX is a
		Registered Trade Mark No 2398667 Patent No. GB
		2383375B Linea-Perlina CFX SS2 is a UK Registered
		Design Cartificate No. 2066588

T: +44 (0)1747 860088

E: info@hamilton-litestat.com | W: www.hamilton-litestat.con

(WFR)

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.