DATASHEET




Code: LTXSS1BG-BGQG

Linea-Tetra CFX | LINEA-TETRA CFX RANGE | Power Sockets

Product Image



Wiring



Dimensions

Insert Type	1 gang 13A Double Pole Switched Socket
Insert Colour	Basalt Gray/Quartz Grey
EAN13 Barcode	5017504092856
Commodity Code	85363010
Luckins TSI	436614167
ETIM Class	EC000125
Dimensions(Nominal)	Single: Height = 91.5mm Width = 91.4mm Depth = 3.8mm
Weight	246 GR
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips
Minimum Wall Box Depth	35mm
Switched Poles	Double
Current Rating	13 Amp
Voltage	220/250V AC
Maximum Load	13 Amp
Mains Frequency	50Hz
IP Rating	IP2XD
ii itatilig	II ZAD
Contact Gap Minimum	3mm
Contact Gap Minimum	3mm
Contact Gap Minimum Terminal Capacity 1	3mm 4x2.5mm²
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2	3mm 4x2.5mm² 3x4mm²
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3	3mm 4x2.5mm² 3x4mm² 2x6mm² Multi-Strand
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4	3mm 4x2.5mm² 3x4mm² 2x6mm² Multi-Strand 1x10mm²
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Earth Terminal Capacity 1	3mm 4x2.5mm² 3x4mm² 2x6mm² Multi-Strand 1x10mm² 4x2.5mm²
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Earth Terminal Capacity 1 Earth Terminal Capacity 2	3mm 4x2.5mm² 3x4mm² 2x6mm² Multi-Strand 1x10mm² 4x2.5mm² 3x4mm²
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3	3mm 4x2.5mm² 3x4mm² 2x6mm² Multi-Strand 1x10mm² 4x2.5mm² 3x4mm² 2x6mm² Multi-Strand
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4	3mm 4x2.5mm² 3x4mm² 2x6mm² Multi-Strand 1x10mm² 4x2.5mm² 3x4mm² 2x6mm² Multi-Strand 1x10mm²
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Product Class 1 Ambient Operating	3mm 4x2.5mm² 3x4mm² 2x6mm² Multi-Strand 1x10mm² 4x2.5mm² 3x4mm² 2x6mm² Multi-Strand 1x10mm² Must be earthed
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Product Class 1 Ambient Operating Temperature	3mm 4x2.5mm² 3x4mm² 2x6mm² Multi-Strand 1x10mm² 4x2.5mm² 3x4mm² 2x6mm² Multi-Strand 1x10mm² Must be earthed -5° to +40°C

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre,

T: +44 (0)1747 860088

E: info@hamilton-litestat.com | **W:** www.hamilton-litestat.cor

F: info@hamilton-lite


All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.

DATASHEET



Code: LTXSS1BG-BGQG

Linea-Tetra CFX | LINEA-TETRA CFX RANGE | Power Sockets



Additional Notes

Dual Earth: Yes

Patents And Trade Marks

Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B

T: +44 (0)1747 860088

: info@hamilton-litestat.com | W: www.hamilton-litestat.cor