DATASHEET



Code: LTXTCMBG-BGQG

Linea-Tetra CFX | LINEA-TETRA CFX RANGE | Telephone and Data Outlets

Product Image




Wiring

Pin No.	BT Wiring Schedule Colour Codes: Striped Wires	
\Box	GREEN / White	
2	BLUE / White	
3	ORANGE / White	
4	WHITE / Orange	
5	WHITE / Blue	
6	WHITE / Green	
Main Wire Colour shown in CAPITALS		

Incoming Telephone Cable On 4 wire systems, Pin 1 and 6 are not connected.

The maximum REN that can be connected to any one exchange line is 4. Any number of sockets may be connected. All sockets are connected in parallel. ie Pin 1 to Pin 1; Pin 2 to Pin 2; etc. as shown in the diagram above.

Dimensions



Insert Type	1 gang Telephone Master
Insert Colour	Quartz Grey
EAN13 Barcode	5017504092979
Commodity Code	85176990
ETIM Class	EC000018
Dimensions(Nominal)	Single: Height = 91.5mm Width = 91.4mm Depth = 3.8mm
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips
Minimum Wall Box Depth	25mm
Switched Poles	N/A
Current Rating	n/a
IP Rating	IP2XD
Contact Gap Minimum	N/A
Earth Terminal Capacity 1	5x1mm²
Earth Terminal Capacity 2	4 x 1.5mm2
Earth Terminal Capacity 3	3 x 2.5mm2
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand
Earth Terminal Capacity 5	1 x 6mm2
Product Class 1	Must be earthed (ref BS7671 415.2.1)
Ambient Operating Temperature	-5° to +40°C
Recommended Location	Internal Use Only
Maximum Installation Altitude	2000m
Standard/Approval	BS 6312:2:2
Patents And Trade Marks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre,