DATASHEET




Code: MCSPWH-W

Metalclad | METALCLAD RANGE | Connection Units


Product Image



Wiring



Dimensions



Local Torri	4 474 De 14 Dele Free 4 Ce
Insert Type	1 gang 13A Double Pole Fused Spur
Insert Colour	White/White
EAN13 Barcode	5017503940332
Commodity Code	85369010
Luckins TSI	405688315
ETIM Class	EC001590
Dimensions(Nominal)	Single: Height = 80.0mm Width = 80.0mm Depth = 41.5mm
Weight	265 GR
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = N/A
Switched Poles	Double
Current Rating	13 Amp
Voltage	220/250V AC
Maximum Load	13 Amp
Mains Frequency	50Hz
Contact Gap Minimum	3mm
Terminal Capacity 1	3x2.5mm²
Terminal Capacity 2	2x4mm² Multi-Strand
Terminal Capacity 3	1x6mm²
Earth Terminal Capacity 1	4x2.5mm²
Earth Terminal Capacity 2	3x4mm²
Earth Terminal Capacity 3	2x6mm² Multi-Strand
Earth Terminal Capacity 4	1x10mm²
Product Class 1	Must be earthed
Ambient Operating Temperature	-5° to +40°C
Recommended Location	Internal Use Only
Standard/Approval	BS 1363-4
Additional Notes	Must be installed using the supplied 40mm deep

Metal Clad back box

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

:: info@hamilton-litestat.com|**W:** www.hamilton-litestat.con

()