DATASHEET

Code: PC1X100LEDAB

Perception CFX - on Transparent Plates | PERCEPTION CFX RANGE | LED Trailing/Leading Edge Push On/Off Rotary Multi-Way Dimmers

Product Image	Item Long Description	
NO IMAGE	Insert Type	1 gang 100W LED Trailing/Leading Edge Push On/Off Rotary Muilt-Way Dimmer
	Insert Colour	Antique Brass
	EAN13 Barcode	5017504005719
	Commodity Code	85365015
	Luckins TSI	398262149
	ETIM Class	EC000025
	Dimensions(Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm
	Switched Poles	Single
Wiring	Current Rating	0.4A
NO IMAGE	Voltage	230V AC
	Maximum Load	5-100W in Trailing Edge / 5-75W in Leading Edge
	Mains Frequency	50Hz
	IP Rating	IP2XD
	Terminal Capacity 1	2X1mm ²
	Terminal Capacity 2	2x1.5mm ²
	Earth Terminal Capacity 1	5x1mm²
	Earth Terminal Capacity 2	4X1.5mm²
	Earth Terminal Capacity 3	3X2.5mm²
Dimensions	Earth Terminal Capacity 4	1X4mm ² Multi-Strand
NO IMAGE	Earth Terminal Capacity 5	1X6mm²
	Product Class 1	Face plate muct be earthed
	Ambient Operating Temperature	-5°C to +40°C
	Recommended Location	Internal Use Only
	Maximum Installation Altitude	2000m
	Standard/Approval	BS EN 60669-2-1
	Additional Notes	Trailing Edge & Leading Edge Dimmer
	Patents And Trade Marks	Perception is a Registered Trade Mark No 2560269 CFX is a Registered Trade Mark No 2398667

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre,

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 18/04/2024 E&OE

Hamilton

making connections beautifully