DATASHEET




Code: WCAC11AB-B

Woods | WOODS RANGE | Hotel Card Switch with LED

Product Image



Wiring



Dimensions

Insert Type	1 gang 10A (6AX) Card Switch On/Off with Blue LED Locator
Insert Colour	Antique Brass/Black
EAN13 Barcode	5017504938918
Commodity Code	85363010
Luckins TSI	391588105
ETIM Class	EC000029
Dimensions(Nominal)	Single: Height = 88.0mm Width = 88.0mm Depth = 13.5mm
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = N/A
Minimum Wall Box Depth	35mm
Switched Poles	Single
Current Rating	10A (6AX)
Voltage	220/250V AC
Maximum Load	10 Amp (6 Amp inductive)
Mains Frequency	50Hz
IP Rating	IP2XD
Contact Gap Minimum	3mm
Contact Gap Minimum Terminal Capacity 1	3mm 3x1mm²
Terminal Capacity 1	3x1mm²
Terminal Capacity 1 Terminal Capacity 2	3x1mm ² 2x1.5mm ²
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3	3x1mm ² 2x1.5mm ² 1x2.5mm ²
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1	3x1mm ² 2x1.5mm ² 1x2.5mm ² 5x1mm ²
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2	3x1mm ² 2x1.5mm ² 1x2.5mm ² 5x1mm ² 4 x 1.5mm2
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3	3x1mm ² 2x1.5mm ² 1x2.5mm ² 5x1mm ² 4 x 1.5mm2 3 x 2.5mm2
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4	3x1mm² 2x1.5mm² 1x2.5mm² 5x1mm² 4 x 1.5mm2 3 x 2.5mm2 1 x 4mm2 Multi-strand
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5	3x1mm² 2x1.5mm² 1x2.5mm² 5x1mm² 4 x 1.5mm2 3 x 2.5mm2 1 x 4mm2 Multi-strand 1 x 6mm2
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating	3x1mm² 2x1.5mm² 1x2.5mm² 5x1mm² 4 x 1.5mm2 3 x 2.5mm2 1 x 4mm2 Multi-strand 1 x 6mm2 Must be earthed
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature	3x1mm² 2x1.5mm² 1x2.5mm² 5x1mm² 4 x 1.5mm2 3 x 2.5mm2 1 x 4mm2 Multi-strand 1 x 6mm2 Must be earthed -5° to +40°C

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

:: info(a)hamilton-litestat.com | **W**: www.hamilton-litestat.cor

(WFR)


All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This dataspeet was generated on 20/04/2024 FSOF

DATASHEET



Code: WCAC11AB-B

Woods | WOODS RANGE | Hotel Card Switch with LED



Additional Notes

Adjustable Time Delay 10 seconds - 5 minutes. Suitable for 44mm and 54mm width Hotel Key Cards

T: +44 (0)1747 860088

: info@hamilton-litestat.com | W: www.hamilton-litestat.cor